

# Use Authentication Mechanisms, Where Appropriate, Correctly

---

William L. Fithen, Software Engineering Institute [vita<sup>3</sup>]

Copyright © 2005 Carnegie Mellon University

2005-10-03

Incorrectly using, or failing to use, authentication mechanisms can introduce vulnerability.

## Description

The following are frequent design defects that produce vulnerable systems:

- Using no authentication when it is required.
- Failure to understand the limitations of the authentication scheme or mechanism. For example, HTTP basic authentication authenticates the user, not the server.
- Failure to separate authentication and authorization.
- Designing passwords that are inherently weak and disallowing passwords that are strong. For example, a system that supports only eight-character passwords composed of alphanumeric characters is a poor design (something that many web sites do) [VU#243592<sup>10</sup>].
- Using weak authentication based on untrustworthy attributes, such as network address information [VU#30308<sup>11</sup>].
- Disabling a subsystem's built-in access controls through identity sharing. This is a common practice in web sites that use back-end databases.
- Failing to propagate authentication across a multi-tier application.
- Designing a secure container for secrets and then exposing the secrets outside the container. This has occurred in several implementations of smart cards.

## Applicable Context

Missing, incomplete, or incorrect application of an authentication mechanism.

## Impacts Being Mitigated

- Impact #1:
  - **Minimally:** The least impact of this vulnerability is unauthenticated access to computing resources.
  - **Maximally:** The greatest impact of this vulnerability depends on the nature of the computing resources. In the worst case, these resources control access to other resources, in which case the result is a complete loss of integrity for the system.

---

3. daisy:320 (Fithen, William L.)

10. #refs

11. #refs

## Security Policies to be Preserved

- Policy #1
  - Access to computing resources is granted only to authentic individuals.

## References

[VU#243592]

Cohen, Cory & Lanza, Jeffrey. *Vulnerability Note VU#243592: Alcatel ADSL modems provide EXPERT administrative account with an easily reversible encrypted password.*  
<http://www.kb.cert.org/vuls/id/243592> (2001).

[VU#30308]

Rafail, Jason. *Vulnerability Note VU#30308: lpd hostname authentication bypassed with spoofed DNS.* <http://www.kb.cert.org/vuls/id/30308> (2001).

## SEI Copyright

Carnegie Mellon University SEI-authored documents are sponsored by the U.S. Department of Defense under Contract FA8721-05-C-0003. Carnegie Mellon University retains copyrights in all material produced under this contract. The U.S. Government retains a non-exclusive, royalty-free license to publish or reproduce these documents, or allow others to do so, for U.S. Government purposes only pursuant to the copyright license under the contract clause at 252.227-7013.

Permission to reproduce this document and to prepare derivative works from this document for internal use is granted, provided the copyright and “No Warranty” statements are included with all reproductions and derivative works.

For inquiries regarding reproducing this document or preparing derivative works of this document for external and commercial use, including information about “Fair Use,” see the [Permissions](#)<sup>1</sup> page on the SEI web site. If you do not find the copyright information you need on this web site, please consult your legal counsel for advice.

## Velden

Naam	Waarde
Copyright Holder	SEI

## Velden

Naam	Waarde
is-content-area-overview	false

---

1. <http://www.sei.cmu.edu/about/legal-permissions.html>

Content Areas	Knowledge/Guidelines
SDLC Relevance	Implementation
Workflow State	Publishable